



CHATHAM BRASS

EASY HEAT PIPE CABLE

PRE-MEASURED AND CUT TO LENGTH PIPE CABLE



- Automatic Thermostat •Copper Shielded •Grounded
- 120 volt •2 foot cold lead with 3 wire plug

Pre-measured Pipe Cable

Model	Watts	Approx Length (Ft.)	Std. Pkg. Qty.	Std. Pkg. Wt.
AHB-013	21	3	10	6#
AHB-016	42	6	10	10#
AHB-019	63	9	10	11#
AHB-112	84	12	10	12#
AHB-115	105	15	10	13#
AHB-118	126	18	5	7#
AHB-124	168	24	5	8#
AHB-130	210	30	5	13#
AHB-140	280	40	5	20#
AHB-160	420	60	5	30#
AHB-180	560	80	5	40#

NEW!!! Cut to Length Pipe Cable

Model	Description	Carton Qty.	Carton Wt.
2502	500" Reel Freeze Free	1	20#
10803	Connection Kit: 1Plug/1Cap	25	5#
HCA	Application Tape 30'	10	2#
EH38	Preset Thermostat	10	3#
FFEC	End Caps: 5 Per Bag	10	2#

Table for Proper Pipe Protection

Method of Installation	Normal Pipe Size	3/8"	1/2"	3/4"	1"	1 1/2"
Straight Along Pipe No Insulation	Degree of Protection	-26°	-15°	-5°	+2°	+8°
Straight Along Pipe with 1/2" Fiberglass Insulation and Waterproof Outer Wrap	Degree of Protection	-45°	-30°	-18°	-8°	0°

- Most installations can be made straight along pipe.
- Spiral installation can be made if cable is a little long. **NEVER OVERLAP PIPE CABLE OR ALLOW IT TO HANG LOOSE!**
- Cable should be strapped to pipe at 6" intervals with Scotch #44 or #33 tape or equivalent.
- Use of 1/2" fiberglass or equivalent pipe insulation with vapor seal is recommended.
- **Plastic Pipe:**
 - Only use on plastic pipe rated for hot water (150° F)
 - Never spiral heating cable on plastic pipe
 - For even heat distribution, wrap plastic pipe with aluminum foil before applying cable.